

IPVcameras

by IPVideo Corporation

- Maximum Resolution
- Easy Installation
- Remarkable Clarity
- Bundled Software



	 1.3 MP Vandal-proof Dome Camera	 1.3 MP - IP Mini-Bullet Camera	 3MP Vandal-proof Dome Camera	 3 MP - IR Mini-Bullet Camera	 2 MP - Fixed Dome IP Camera
Image Sensor	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS
Lens	4mm @ F2.0	6mm @ F2.0	4mm @ F2.0	6 mm @ F2.0	2.7 ~ 9 mm @ F1.2 Angle of view: 101° ~ 30.4° Remote focus
Angle of View	52°	45.3°	52°	45.3 °	none
Day & Night	IR cut filter	IR cut filter with auto switch	IR cut filter with auto switch	IR cut filter with auto switch	Electronic (IR cut filter with auto switch)
Min. Illumination	0.01 Lux @ F1.2, AGC ON 0.02* Lux @ F2.0, AGC ON 0 Lux with IR	0.01 Lux @ F1.2, AGC ON with IR 0.02* Lux @ F2.0, AGC ON with IR	0.05 Lux @(F1.2,AGC ON), 0 Lux with IR 0.15 Lux @(F2.0,AGC ON), 0 Lux with IR	0.05 Lux @(F1.2,AGC ON), 0 Lux with IR 0.15 Lux @(F2.0,AGC ON), 0 Lux with IR	0.5 Lux @ F1.2, AGC on, 0.1 Lux @ F1.2, AGC on
Video Compression	H.264/MJPEG	H.264 / MJPEG	H.264/MJPEG	H.264 / MJPEG	MJPEG / H.264
Max Image Resolution	1280x960	1280x960	2048 x 1536	2048 x 1536	NA
Frame Rate	30 fps (1280x960), 30 fps (1280x720)	30 fps (1280x960), 30 fps (1280x720)	50Hz: 12.5fps(2048 x 1536),25fps(1920 x 1080), 25fps (1280 x 720) 60Hz: 15fps (2048 x 1536),30fps(1920 x 1080), 30fps (1280 x 720)	50Hz: 12.5fps(2048 x 1536),25fps(1920 x 1080), 25fps (1280 x 720) 60Hz: 15fps (2048 x 1536),30fps(1920 x 1080), 30fps (1280 x 720)	60HZ: 25fps (1280x720), 25fps (1280x960), 1 2.5fps (1600x1200), 30fps (704x480)
Audio In/Out	NA	NA	NA	NA	1ch microphone input, 3.5mm mini-jack/1ch 3.5mm audio interface (line level, 600 Ω)
Alarm Trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark	Password protection and watermark
Network Storage	NAS (iSCSI optional)	NAS (iSCSI optional)	NAS (iSCSI optional)	NAS (iSCSI optional)	NA
Power Supply	12 VDC ± 10%, PoE (802.3af)	12 VDC ± 10%, PoE (802.3af)	12 VDC ± 10%, PoE (802.3af)	12 VDC ± 10%, PoE (802.3af)	12 VDC ± 10%, PoE (802.3af)
Weather Proof Rating	IP66	IP66	IP66	IP66	none
Part #	VSA-14	VSA-15	VSA-34	VSA-35	VSA-44
MSRP	\$288	\$288	\$338	\$338	\$741