


2000 SERIES PRO2 VIDEO SERVER

Powerful, purpose-built devices with minimal downtime

The 2000 Series PRO2 video server, from IPVideo, is a powerful, purpose-built device designed to support the most demanding video-centric software applications. Pre-loaded with the IPVideo enterprise-scale **SentryVMS**® or **Mosaic**® video management software, **C3fusion**® for command center integrations, and **AVfusion**® audio/video recording software, this server is ready to deliver exceptional performance of each application, when unlocked by the user.

Count on minimal downtime, with the superior engineering, exceptional hardware design and components of the 2000 Series PRO2. Plus, this video server is backed by a three year warranty and xConnect management software.



KEY FEATURES

- 100 Mbps performance
- **SentryVMS**® or **Mosaic**® video management software
- **C3fusion**® for command center integrations
- **AVfusion**® audio/video recording software
- **xConnect Server Agent** is designed to monitor, report and manage the environment and performance on server hardware

KEY BENEFITS

- Accelerated installation with pre-loaded IPVideo applications
- Built in Health Monitoring
- Three Year Warranty
- Next Business Day Support available



IPVIDEO 2000 SERIES

P/N: PRO2R

SYSTEM

Processor	4th generation Intel® Core™ i3-4460 Processor
Operating System	Window 10 IoT Value
Motherboard	ASUS® B8M-E/CSM/SI
Memory	8GB DDR3 1333MHz ECC Unbuffered
Operating System Storage	240GB Intel® SSD 540 Series
Maximum Raw Storage	Up to 2TB
Networking	2 × 1GbE LAN Port Standard
Front I/O Ports	2 × USB 2.0
Rear I/O Ports	2 × USB 3.0 8 × USB 2.0 1 × LAN (RJ45) port 1 × Audio jack 2 × PS/2 1 × VGA 1 × DVI-D
Graphics*	Intel® HD Graphics or Optional Discrete Video Card
Video Output	DVI-D: 1920 × 1200 @ 60 Hz
Maximum Resolution	VGA: 1920 × 1200 @ 60 Hz
Hardware Monitoring	Pre-installed with xConnect Server Agent
Peripherals	Microsoft® Keyboard and Mouse
Warranty	3 Year Depot Warranty, NBD Warranty available as an option

MECHANICAL

Form Factor	Small Form Factor
OS Drive Bays	1 × mSATA
Data Drive Bays	2 × 3.5" Fixed, Internal
Power Supply	115 ~ 230 V
Watts / BTU per Hour	300W
AC Input VAC Freq	50 ~ 60 Hz
Dimensions	3.9 × 12.75 × 17 inches 99 × 324 × 432 millimeters

* Graphics card is dependent upon processor

